

Technical Specifications: UC^X450

System Processor:

- Built-in Intel® Pentium™ G850 (2.9GHz) Processor

Network:

- Dual Gigabit/100/1000T Ethernet

Hard Drive and Memory:

- 500G Serial ATA 3 Gbps Hard Drive
- 4Gb RAM

Additional Interfaces

- Trunk Expansion Slot (1)
- USB, HDMI, e-SATA (for external back-up)
- Supported Trunk Cards:
 - T1/E1 PRI trunk card (1, 2 or 4 span)
 - 4-port FXO trunk card
 - 8-port FXO trunk card
 - BRI trunk card

System Cooling

- PowerEdge Heat sink on CPU
- Variable speed 1.6" fans (4)

Power:

- 250W power supply with cord.

Dimensions:

- 15.5"(L) x 17.1"(W) x 1.7" (H) – 1U

Shipping Parameters

- Dimensions: 32" X 24" X 10" (81x61x25cm)
- Weight: 30Lbs (13.6 Kg)

Maximum Number of Extensions:

- UC^X450 supports a maximum of 450 extensions (225 concurrent calls)

System Recording Capacity:

- 7,000 hours for Call Recording and Voicemail

Supported Telephony Devices:

- Supported Nortel telephones:
 - Nortel 1100, 1200 & 2000 series, i2050 softphone
 - Nortel T/M series digital telephones
 - Nortel M3900, M2000 series digital telephones
- Mobility – 4G, SIP Wifi
 - iPhone, Android, handheld/tablet
- Supported SIP telephones:
 - Yealink, Polycom, Cisco, Counterpath BRIA
- FXS/FXO, T1/E1 Gateways – Grandstream, Digium
- GSM – E-MetroTel Gateway

