

# Technical Specifications: UC<sup>X</sup>1000

## System Processor:

- Intel® Xeon™ E5620 12Mb cache (2.4GHz) Processor

## Network:

- Dual Gigabit 10/100/1000T Ethernet

## Hard Drive and Memory:

- Raid 1 Dual 1Tb Hard Disks, 3.5" hot pluggable
- Total drive bays (8), 6 open
- 8Gb RAM

## Additional Interfaces:

- Trunk Expansion Slot (3)
- USB, HDMI, e-SATA
- Supported Trunk Cards: (up to 3)
  - T1/E1 PRI trunk card (1, 2 or 4 span)
  - 4-port FXO trunk card
  - 8-port FXO trunk card
  - BRI trunk card

## System Cooling

- PowerEdge Heat sink
- Variable speed 1.6" fans (8)

## Power:

- Dual 250W power supplies with cords.

## Dimensions:

- 25"(L) x 17.1"(W) x 3" (H) – 2U

## Shipping Parameters

- Dimensions: 36" X 24" X 12" (91x61x30cm)
- Weight: 60Lbs (27.3 Kg)

## Maximum Number of Extensions:

- UC<sup>X</sup>1000 supports a maximum of 1000 extensions (500 concurrent calls)

## System Recording Capacity:

- 16,000 hours for Call Recording and Voicemail

## Supported Telephony Devices:

- Supported Nortel telephones:
  - Nortel 1100, 1200 & 2000 series, i2050 softphone
  - Nortel T/M series digital telephones
  - Nortel M3900, M2000 series digital telephones
- Mobility – 4G, SIP Wifi
  - iPhone, Android, handheld/tablet
- Supported SIP telephones:
  - Yealink, Polycom, Cisco, Counterpath BRIA
- FXS/FXO, T1/E1 Gateways – Grandstream, Digium
- GSM – E-MetroTel Gateway

